L Number	Hits	Search Text	DB	Time stamp
2	15	5745624.pn. or 5077878.pn. or 5163108.pn. or 5896481.pn. or 5602955.pn. or	USPAT; US-PGPUB	2004/08/18 13:44
3	0	5881198.pn. or 5412748.pn. or 6216939.pn. or 4798439.pn. or 4779788.pn. or 4741796.pn. or 4663652.pn. or 4008948.pn. or 5559918.pn. (5745624.pn. or 5077878.pn. or 5163108.pn. or 5896481.pn. or 5602955.pn. or 5881198.pn. or 5412748.pn. or	USPAT; US-PGPUB	2004/08/18 14:08
• .		6216939.pn. or 4798439.pn. or 4779788.pn. or 4741796.pn. or 4663652.pn. or 4174491.pn. or 4008948.pn. or 5559918.pn.) and (mount with aperture)		
4	0		USPAT; US-PGPUB	2004/08/18 13:48
5	0	• '	USPAT; US-PGPUB	2004/08/18 13:51
6	1		USPAT; US-PGPUB	2004/08/18 13:53
7		·	USPAT; US-PGPUB	2004/08/18 13:53
8	0		USPAT; US-PGPUB	2004/08/18 13:47
9	1	(5745624.pn. or 5077878.pn. or 5163108.pn. or 5896481.pn. or 5602955.pn. or 5881198.pn. or 5412748.pn. or 6216939.pn. or 4798439.pn. or 4779788.pn. or 4741796.pn. or 4663652.pn. or 4174491.pn. or 4008948.pn. or 5559918.pn.) and (high with (thermal adj conductivity))	USPAT; US-PGPUB	2004/08/18 14:27

10	9447	, , , , , , , , , , , , , , , , , , , ,	USPAT;	2004/08/18
		conductivity))	US-PGPUB	13:48
11	1	(USPAT;	2004/08/18
		conductivity))) and (mount with fiber	US-PGPUB	13:50
		with directly)		
12	9325	(385/14,32,52-56,49,58-60,63,66,69-78,88-9		
			US-PGPUB	13:51
13	38	(
		and (mount with aperture)	US-PGPUB	13:51
14	3	[(((000, 00, 00, 00, 00, 00, 00, 00, 00,		
		and (mount with aperture)) and (mount	US-PGPUB	13:52
		with fiber with direct\$4)		
15	40	[9 USPAU ;137).	
		and (mount with fiber with solder\$5)	US-PGPUB	14:08
16	2	(((385/14,32,52-56,49,58-60,63,66,69-78,88	-BSPAB6,137)	
		and (mount with fiber with solder\$5)) and	US-PGPUB	14:09
		(mount with fiber with housing)		
17	0	[((((,,,,,,,,	B USPAT 36,137	
	ļ	and (mount with fiber with solder\$5)) and	US-PGPUB	14:08
		(mount with fiber with housing)) and		
18	2157	(m305114182,52e5648)58-60,63,66,69-78,88-	9 USPAB ;137).	
	Ì	and solder\$5	US-PGPUB	14:09
19	2	((((,,,)2000-4/50.8/18
		and (mount with fiber with solder\$5)) and	US-PGPUB	14:09
		(mount with fiber with housing)) and		
20	0	44440=#==/0=/0=/00/00/00/00/00/00/		
		and (mount with aperture)) and (ceramic	US-PGPUB	14:27
		with (high near3 (thermal adj		
21	0	¢¢nda6±14;8₽)\$2-56,49,58-60,63,66,69-78,88		
		and (mount with aperture)) and (ceramic	US-PGPUB	14:28
		with (thermal adj conductivity))		
22	1932	(alumina or berylium) and (ceramic with	USPAT;	2004/08/18
		(thermal adj conductivity))	US-PGPUB	14:28
23	717	, ,	USPAT;	2004/08/18
		(high near3 (thermal adj conductivity)))	US-PGPUB	14:28
24	10	((385/14,32,52-56,49,58-60,63,66,69-78,88-	9 U \$PAG;137).	
		and ((alumina or berylium) and (ceramic	US-PGPUB	14:29
		with (high near3 (thermal adj		

conductivity))))